Slip rings

Slip rings in the standard version are manufactured in phosphor bronze grade PB1 acc. BS 1400. GZ - Cu Sn7 Zn Pb DIN 1705.

Copper nickel are as shown in the table below. Insulation of DMC, reinforced with polyester-based glassfiber.

The table lists the dimensions and most common types of slip rings we usually stock for immediate delivery.







Item number	Product type	Number rings	D.	S.	Standard-hole Ø	Max Ø bore	L.	a.	b.	c.	e.	R.	Fxf	h
126070	2-60-10-25	2	60	10	25	28	44	6.8	6.8	10	47	M5, M6	-	10
126071	2-70-10-31,75	2	70	10	31.75	33	36	6	6	5	48	4Ø	10x1	12
126072	3-52-10-25,4	3	52	10	25.4	28	52	7	7	1	40	-	5x1	7
126073	3-80-12-38,1	3	80	12	38.1	45	69.5	12.4	4	4	47	M5	-	15
126079	3-115-20-45-57	3	115	20	45–57	-	112	15	-	-	85	M8	-	25
126077	3-120-12,7-58*	3	120	12.7	58	73	76.3	12	6.5	6	-	M8	-	18
126078	3-127-19-34,9	3	127	19	34.9	83	89.3	9.5	7.8	4.6	96	M6, M8	-	15
126074	4-52-10-25,4	4	52	10	25.4	26	64	7	1	1	40	-	5x1	14
126075	4-70-10-34,8	4	70	10	34.8	36	68	6	5	4.5	48	4Ø	10x1	12

* Copper nickel rings

Slip rings not shown in the table can be manufactured. Request price details.

How to contact BEVI
Contact details for all countries are continually updated on our website.
Please visit www.bevi.com to access the information direct.

BEVI AB (Headquarters)
Blomstermåla, Sweden
Tel. +46 499 271 00
info@bevi.se

B00157-2022-01 EN

BEVI is a registered trademark owned by BEVI AB. BEVI reserves the right to change specifications without prior notice.