

A flexible binding tape for winding applications.
Braided fiberglass thread, unvarnished.



Typical applications

Suitable for use in electrical and electronic constructions, electrical machinery and motors class C.

Properties

- Withstands liquid fuels, no degradation
- Highly flexible
- Resistant to transformer oils in acc. with UTEC 93641
- Not watertight
- Suitable for Class C varnishes

Composition

Braided fiberglass yarn, unvarnished

Colour

Standard: White

Packaging

Bobbins:

- Ø 0.5 mm to 4 mm, rolls of 200 m
- Ø 5 mm to 12 mm, rolls of 100 m
- Ø 14 mm to 20 mm, rolls of 50 m
- Ø 22 mm to 100 mm, rolls of 25 m
- Ø 100 mm to 200 mm, rolls of 15 m

Technical data

- Temperature class C 450°C
- Working temperature -60°C to +450°C
Intermittent +550°C (a few hours)
- Breakdown voltage 0.5 kV to 1.5 kV depending on wall thickness

Approvals, standards

- NF EN 60684-1 (10-2003)
- NF EN 60684-2 (07-2012)

Item number	Internal Diameter (mm)	Min Diameter int (mm)	Max Diameter int (mm)	Wall Thickness approx. (mm)
125743	3	2.8	3.2	0.28
125744	6	5.7	6.3	0.32
125745	8	7.6	8.4	0.40
125746	10	9.5	10.5	0.45
125747	12	11	13	0.40
125748	14	13	15	0.50
125749	16	15	17	0.50

How to contact BEVI

Contact details for all countries are continually updated on our website.
Please visit www.bevi.com to access the information direct.

BEVI AB (Headquarters)
Blomstermåla, Sweden
Tel. +46 499 271 00
info@bevi.se