

Vidatape S is a terylene tape with very high shrinkability at elevated temperature. It is particularly suited for banding of all types of electrical equipment.

The tape comes with a black identification line.



Typical applications

Suitable for the binding of spools, reels and coil ends in electric motors as well as electrical applications where high controlled shrinkage is required. Terylene tape is excellent for manual wrapping and banding where glass tape can cause skin irritation.

Properties

- High varnish and resin absorption capacity
- Easy to work with
- Good rigidity

Composition

Woven tape constructed of polyethylene terephthalate yarns that cause shrinkage when subjected to elevated temperatures

Colour

White with black identification line.

Technical data

- Temperature class F, 155°C, intermittent +200°C
- Max elongation: 25 N/mm
- Weight g / m²: 98
- Tolerance in width: ±1 mm
- Shrinkage at 150°C: 12.5 %
- Thickness: 0.13 -0.01 +0.04 mm

Item number	Dimensions (mm)	Packaging
125739	0.13 x 13	50 m / roll
125740	0.13 x 20	50 m / roll
111291	0.13 x 25	50 m / roll
111293	0.13 x 30	50 m / roll
111294	0.13 x 38	50 m / roll
125741	0.13 x 50	50 m / roll

How to contact BEVI

Contact details for all countries are continually updated on our website.
Please visit www.bevi.com to access the information direct.

BEVI AB (Headquarters)
Blomstermåla, Sweden
Tel. +46 499 271 00
info@bevi.se