

Reinforced and strengthened glassfiber tape for oil-filled transformers, spools and electric motors.



### Typical applications

Transformers, spools and electric motors.

### Properties

- Reinforced and strengthened
- Dielectric strength 4.5 kV

### Composition

- Polyester film-glassfiber/adhesive agent: acrylic

### Colour

- Transparent

### Packaging

- On rolls of 50 m (tolerance -0 m/+1 m)
- Tolerance width  $\pm 0.2$  mm
- Inner core of roll 76 mm  $\pm 3\%$
- Storability 12 months

### Technical data

- Acrylic adhesive agent that withstands high temperatures, ageing and also resistant to solvents.
- Working temperature: +155°C
- Max elongation: 5%
- Tensile strength: 150 N/cm
- Thickness: 0.13 mm  $\pm 10\%$
- Dielectric strength: 4.5 kV
- Bond strength on steel: 3.5–4.5 N/cm

### Approvals, standards

- Test methods AFERA, PSTC, IEC EN 60454-2

Item number	Dimensions
126252	15 mm × 50 m
126253	25 mm × 50 m
126254	65 mm × 50 m

### How to contact BEVI

Contact details for all countries are continually updated on our website.  
Please visit [www.bevi.com](http://www.bevi.com) to access the information direct.

BEVI AB (Headquarters)  
Blomstermåla, Sweden  
Tel. +46 499 271 00  
[info@bevi.se](mailto:info@bevi.se)